



Metaltex Teknoloji Kimyasal Urunler San. ve Tic. Ltd. Sti.

Address : Ostim Mahallesi Alinteri Bulvari Gul 86 Sanayi Sitesi No:1/49
06370, OSTIM/ANKARA, TURKEY

Phone : +90 312 385 52 01 - 03 Fax : +90 312 385 52 02

Web : www.metaltexkimya.com.tr

MT- COOL OIL

GRINDING FLUID



Description:

MT- Cool Oil is a liquid compound formulated for Grinding operations at surface grinding machines. MT-Cool Oil contains organic chemicals and surface agents, it provides cooling and sliding while operating processes as well as protect parts against corrosion for short periods.

Benefits:

MT-Cool Oil offers these benefits:

1. Non-flammable in liquid form.
2. Readily soluble in hard and soft water at recommended concentrations.
3. Free of chromate and phenols.
4. Readily rinses from parts with hot or cold water.
5. Easy to control solution by simple reflectometer.

Use instructions:

MT- Cool Oil is used 30 -50 g/lit (3-5 %) of concentration in water.

Physical Properties:

pH (50 g/lit, 25 °C) = 9,00-10,00

Density (pure, 25 °C) = 1,00-1,10 g/ml

Disposal information:

Dispose of spent solution per local, state and regional regulations.

Caution:

MT- Cool Oil contains organic compounds. Avoid contact with eyes, skin and clothing. Do not take internally. Consult Material Safety Data Sheet before use.

Packaging

Packaged in 35 kg (77 lb) or 200 kg (440 lb) drum

Storage

Store, dry area between +5, +40. Keep container closed when not in use.

Notice:

The above information and recommendations concerning this product are based upon our laboratory tests and field use experience. However, since conditions of actual use are beyond our control, any recommendations or suggestions are made without warranty, express or implied. Manufacturer's and seller's sole obligation shall be to replace that portion of the product shown to be defective. Neither shall be liable for any loss, damage, or injury, direct or consequential, arising out of the use of this product.